


01: Level			
Member Name	Results	Current Solution	Comments
BM1	Passed	3 Piece(s) 1 3/4" x 18" 2.0E Microllam® LVL	

Forte Software Operator	Job Notes
Garrett Bumgardner Builders First Source (904) 680-6222 garrett.bumgardner@bldr.com	Starr Custom Homes Sieburg Residence

9/13/2016 11:40:23 AM Forte v5.0, Design Engine: V6.4.0.40 *Job.4te*

Overall Length: 22 0 8



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.; Drawing is Conceptual

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	7727 @ 0 2 0	13781 (3.50")	Passed (56%)		1.0 D + 1.0 Lr (All Spans)
Shear (lbs)	6471 @ 1 9 8	22444	Passed (29%)	1.25	1.0 D + 1.0 Lr (All Spans)
Moment (Ft-lbs)	41299 @ 11 0 4	72662	Passed (57%)	1.25	1.0 D + 1.0 Lr (All Spans)
Live Load Defl. (in)	0.364 @ 11 0 4	0.724	Passed (L/716)		1.0 D + 1.0 Lr (All Spans)
Total Load Defl. (in)	0.737 @ 11 0 4	1.085	Passed (L/354)		1.0 D + 1.0 Lr (All Spans)

System : Floor Member Type : Flush Beam Building Use : Residential Building Code : IBC Design Methodology : ASD

• Deflection criteria: LL (L/360) and TL (L/240).

• Bracing (Lu): All compression edges (top and bottom) must be braced at 9 10 2 o/c unless detailed otherwise. Proper attachment and positioning of lateral bracing is required to achieve member stability.

	Bearing			Loads to Supports (lbs)				
Supports	Total	Available	Required	Dead	Floor Live	Roof Live	Total	Accessories
1 - Column - SYP	3.50"	3.50"	1.96"	3913	441	3813	8167	None
2 - Column - SYP	3.50"	3.50"	1.96"	3913	441	3813	8167	None

		Tributary	Dead	Floor Live	Roof Live	
Loads	Location	Width	(0.90)	(1.00)	(non-snow: 1.25)	Comments
1 - Uniform (PSF)	0 0 0 to 22 0 8	100	12.0	40.0	-	Residential - Living Areas
2 - Uniform (PLF)	0 0 0 to 22 0 8	N/A	65.0	-	110.0	T05, T06
3 - Uniform (PLF)	0 0 0 to 22 0 8	N/A	110.0	-	-	Wall Above
4 - Uniform (PLF)	0 0 0 to 22 0 8	N/A	142.0	-	236.0	T42

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Refer to current Weyerhaeuser literature for installation details. (www.woodbywy.com) Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC ES under technical reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports refer to http://www.woodbywy.com/services/s_CodeReports.aspx.

The product application, input design loads, dimensions and support information have been provided by Forte Software Operator

Forte Software Operator	Job Notes
Sarrett Burngardner Juilders First Source 904) 680-6222 jarrett.burngardner@bldr.com	Starr Custom Homes Sieburg Residence

9/13/2016 11:40:23 AM Forte v5.0, Design Engine: V6.4.0.40 *Job.4te*

SUSTAINABLE FORESTRY INITIATIVE