

Job 932704	Truss F13	Truss Type Floor	Qty 6	Ply 1	Job Reference (optional) T10033719
---------------	--------------	---------------------	----------	----------	---------------------------------------

Builders FirstSource, Jacksonville, FL 32244

7.640 s Apr 19 2016 MiTek Industries, Inc. Mon Dec 12 14:15:13 2016 Page 1
ID:iZ63XLbsXieEZHru0kDJoiyXpzq-oezNbuEi67WifbLElkDejHgS5ezprSuxp3e2YQy9i2y

0-1-8



0-1-8
Scale = 1:26.8




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [8:0-1-8,Edge]

LOADING (psf)	SPACING-		CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	2-0-0	TC 0.64	Vert(LL) -0.17	13-14	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.00		BC 0.85	Vert(TL) -0.25	13-14	>748	240		
BCLL 0.0	Rep Stress Incr YES		WB 0.51	Horz(TL) 0.05	9	n/a	n/a		
BCDL 5.0	Code FBC2014/TPI2007		(Matrix)					Weight: 83 lb	FT = 11%F, 11%E

LUMBER-

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 16=834/0-5-0, 9=834/0-5-0

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 16-17=-829/0, 1-17=-828/0, 9-18=-829/0, 8-18=-828/0, 1-2=-832/0, 2-3=-1985/0, 3-4=-2616/0, 4-5=-2616/0, 5-6=-2616/0, 6-7=-1985/0, 7-8=-832/0
BOT CHORD 14-15=0/1562, 13-14=0/2379, 12-13=0/2616, 11-12=0/2379, 10-11=0/1562
WEBS 1-15=0/1072, 2-15=-1016/0, 2-14=0/588, 3-14=-549/0, 3-13=0/563, 4-13=-276/0, 8-10=0/1072, 7-10=-1016/0, 7-11=0/588, 6-11=-549/0, 6-12=0/563, 5-12=-276/0

NOTES- (5)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x3 MT20 unless otherwise indicated.
- 3) "Semi-rigid pitchbreaks including heels" Member end fixity model was used in the analysis and design of this truss.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 5) This manufactured product is designed as an individual building component. The suitability and use of this component for any particular building is the responsibility of the building designer per ANSI TPI 1 as referenced by the building code.

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314. **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**




6904 Parke East Blvd.
Tampa, FL 36610

Job 932704	Truss T25	Truss Type Roof Special	Qty 1	Ply 1	Job Reference (optional)	T10033749
---------------	--------------	----------------------------	----------	----------	--------------------------	-----------

Builders FirstSource, Jacksonville, FL 32244

7.640 s Apr 19 2016 MiTek Industries, Inc. Mon Dec 12 14:15:31 2016 Page 1

ID:Z63XLbsXieEZHRu0kDJ0iyXpzq-H63BN1S?tfncpMjioWYsS4QZyuB83ciays0?BNy9i2g



Scale: 3/16"=1'

Plate Offsets (X,Y)-- [5:0-3-8,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.55	Vert(LL)	0.04	5-6	>999	MT20	244/190
TCDL 7.0	Plate Grip DOL 1.25	BC 0.52	Vert(TL)	-0.03	5-6	>999		
BCLL 0.0 *	Lumber DOL 1.25	WB 0.42	Horz(TL)	-0.00	4	n/a		
BCDL 5.0	Rep Stress Incr NO	(Matrix-M)						
	Code FBC2014/TP12007						Weight: 63 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except*
 2-6: 2x4 SP M 31

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-11-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 8-8-5 oc bracing.
 WEBS 1 Row at midpt 3-5, 2-6, 2-5

REACTIONS.

(lb/size) 6=235/0-5-8, 4=872/0-3-0
 Max Horz 6=-320(LC 10)
 Max Uplift 6=-260(LC 10), 4=-225(LC 9)
 Max Grav 6=357(LC 9), 4=1271(LC 19)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-6=-923/719
 BOT CHORD 5-6=-446/379
 WEBS 2-5=-964/1134

NOTES- (8)

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=25ft; Cat. II; Exp C; Encl., GCpi=0.18; MWFRS (envelope) and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 6=260, 4=225.
- 5) Load case(s) 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 6) "Semi-rigid pitchbreaks including heels" Member end fixity model was used in the analysis and design of this truss.
- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 886 lb down and 71 lb up at 4-5-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 8) This manufactured product is designed as an individual building component. The suitability and use of this component for any particular building is the responsibility of the building designer per ANSI TPI 1 as referenced by the building code.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
 Uniform Loads (plf)
 Vert: 1-2=-54, 2-3=-54, 4-6=-10
 Concentrated Loads (lb)
 Vert: 4=-781

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314. **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**



6904 Parke East Blvd.
 Tampa, FL 36610

Job 932704	Truss T47	Truss Type Scissor	Qty 6	Ply 1	Job Reference (optional)	T10033769
---------------	--------------	-----------------------	----------	----------	--------------------------	-----------

Builders FirstSource, Jacksonville, FL 32244

7.640 s Apr 19 2016 MiTek Industries, Inc. Mon Dec 12 14:15:49 2016 Page 1
ID:iZ63XLbsXieEZHRu0kDJ0iyXpzzq-lZ8_8BgHdB2e_759sls5AtAcq9OfHnTE5fNypLy9i2O




Plate Offsets (X,Y)-- [1:0-1-2,0-1-6], [3:0-1-2,0-1-6]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.65	Vert(LL)	0.06	4-7	>999	MT20	244/190
TCDL 7.0	Plate Grip DOL 1.25	BC 0.31	Vert(TL)	-0.10	4-7	>999		
BCLL 0.0 *	Lumber DOL 1.25	WB 0.28	Horz(TL)	0.06	3	n/a		
BCDL 5.0	Rep Stress Incr YES	(Matrix-M)						
	Code FBC2014/TPI2007						Weight: 78 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3, Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-3-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=509/0-5-8, 3=509/0-5-8
Max Horz 1=159(LC 9)
Max Uplift 1=131(LC 12), 3=131(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-1058/436, 2-3=-1058/436
BOT CHORD 1-4=-215/847, 3-4=-215/835
WEBS 2-4=-205/735

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=25ft; Cat. II; Exp C; Encl., GCp=0.18; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 3 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=131, 3=131.
- "Semi-rigid pitchbreaks including heels" Member end fixity model was used in the analysis and design of this truss.
- This manufactured product is designed as an individual building component. The suitability and use of this component for any particular building is the responsibility of the building designer per ANSI TPI 1 as referenced by the building code.

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.



6904 Parke East Blvd.
Tampa, FL 36610